

01.9010 – LCDPC M-TOUCH HANNSPREE SN22A1 21.5" LEDFHD SLIM ATOMD510 3GBDDR2
320SATA2.5" W7PRE DVD±RWDL CARDR HDMI/VGA GLAN WIFI CAM BT 4USB

Galleria fotografica



Caratteristiche e dati tecnici

Codice articolo del produttore: SN22A1

Operating System: Windows 7 Home Premium

Processor: Intel D510

Chipset: NM10

Memory: 3GB/DDR2 800MHz SO-DIMM

Storage

Hard Drive: SATA 320GB/5,400rpm

ODD: DVD Super Multi/Tray Type

Card Reader: Built-in 4-in-1 card reader(MS/MS-Pro/SD/MMC)

Video GPU: Intel GMA 3150 Express Chipset Family

Monitor Specification

Brightness: 250 nits (Typical) LED Panel, AUO

Contrast: 1000:1 (Typical)

Response Time: 5ms (Typical)

Viewing Angle: 170/160 (Typical: H/V)

Support Color: 16.7M Colors (RGB 6-bit + Hi_FRC)

Video Interface Panel: Dual Channel LVDS

Video Input

Analog: RGB Analog (75 ohms, 0.7 Vp-p)

Digital: HDMI (TMDS, 100 ohms)

Frequency: Fh: 30~83KHz, Fv: 50~75Hz

Video Bandwidth: 1920 x 1080p, 60~24bit=148.5MHz (Max)

Sync: H/V separated (TTL)

Compatibility PC: VGA/HDMI up to 1920 x 1080

OSD Language: Iconic

PC Input Range

Horizontal Freq.: 30~83KHz

Vertical Freq.: 50~75Hz

Max. Display Frequency(Resolution H*V/Fv): 1920 x 1080p pixels @ 60Hz

Communication

LAN 10/100/1000: Base-Ethernet LAN on Board

WLAN: WLAN (802.11 b/g/n)

Bluetooth: Bluetooth (2.1, Class II)

Webcam: 1.3M Pixels + Digital MIC

Adjustment

Tilt: 10°~55°

Optical Touch Module Spec



DISTRIBUZIONE INFORMATICA

Principle: 2 sensor assemblies with FFCs attached, 4 light guides around touch screen, 1 controller PCBA
Sensor Refresh Rate: 100Hz
Resolution: 32K x 32K (USB HID)
Accuracy: >95% @5mm 2-Point @2.5mm single-Point
Glass Thickness: 1.9mm
Stylus Size: Pointers minimum diameter 6 mm
Calibration: Each touch panel will be executed factory calibration before shipment. End-user calibration is not required.
Interface: USB 1.1 full speed (12 Mbps); USB bulk transfer.
OS Support Windows 7: Microsoft device logo for Win7 multi-touch – Vista: Digitizer or digitizer touch

Touch Module Power

Consumption
Operating: < 2.5W; Suspend: < 12.5mW
Glass Hardness: >= 7 Moh s hardness rating
Light Transmission: >= 88% No coating

Interface

Adaptor (DC Jack), RJ-45 LAN, Line in, Headphones, Microphone, USB 2.0*4, DSub, HDMI CTS1.4a Test

Audio

Sound: Effect 3D stereo enhanced sound system (hardware ready)
Speaker: 2W x 2
Headphones: Yes
Microphone: Yes

Power Consumption (on / standby / off)

On: < 65W; Standby: < 2W; Off: < 1W
AC Power Range Input AC 100-240, 50-60Hz 1.5A; Output DC19V/3.42A

Power Mode / Indicator

Light
Power on: blue; Sleep mode: blinking;
Power off: off

Operating Condition

Temperature 0 to 35 degree
Humidity 10% ~ 85%

Physical Dimension (W*D*H mm): 52.74 x 40.49 x 7.24 mm (including stand)

Packing Dimension (W*D*H mm): 59.4 x 16.1 x 49.3 mm

Net Weight: 6.1 Kg

Gross Weight: 8.5 Kg

Tilt: 10° to 55° degree for hinge tilt

Kensington Lock: Yes

Controls Front Control Brightness +/-, Volume +/-, Power, Video source switch, Auto adjustment, Color mode

Container Loading 40 Standard 1008 20 Standard 480

Accessory Power Cord (1.8m), Recovery DVD, Driver DVD, User Manual, Quick Start Guide, Warranty Card

Included Software Windows Live Essentials, Office Starter 2010, YouPaint, YouCam, YouMemo, Power2Go, Acrobat PDF Reader

Green Product: Yes

HDMI Logo: HDMI CTS1.4a

Certification: CE, CB, Energystar 5.0, WEEE, RoHS, REACH, ErP lot 6 (meet Off mode), Safety model no.: HSG1161

Codici a barre



La società declina ogni responsabilità riguardo all'accuratezza delle informazioni riportate in questa pagina per errori tipografici o errori di altro tipo o per omissioni nel contenuto. I marchi riportati sono dei legittimi proprietari.